

Super King™ Long Shank Hose Couplings
Female NPSM Couplings

Application:

- for liquid transfer where steel and stainless are preferred

Size	Shank Length	Plated Steel Shank with Brass Pin Lug Nut ¹ Part #	Plated Steel Shank with Iron Pin Lug Nut ¹ Part #
1¼"	4⅞"	SD15	SDMP15
1½"	4⅞"	SD20	SDMP20
2"	5"	SD25	SDMP25
2½"	5"	SD30	SDMP30
3"	5"	SD35	SDMP35
4"	5"	SD40	SDMP40

Size	Shank Length	316 Stainless Shank with Iron Pin Lug Nut ¹ Part #	316 Stainless Shank with Stainless Hex Nut ² Part #
1½"	4⅞"	---	RSHR20
2"	5"	RSDM25	RSDR25
3"	5"	RSDM35	---

¹ KLW leather gaskets standard

² PTFE gaskets standard

Industrial Hose Fittings



pin lug nut




hex nut

Male NPT Couplings

Size	Shank Length	Plated Steel Part #	316 Stainless Part #
1¼"	4-3/8"	SK16	---
1½"	4-5/32"	SK21	---
2"	5-5/16"	SK26	RSK26
2½"	5-5/16"	SK31	---
3"	5-1/2"	SK36	RSK36
4"	5-1/2"	SK46	---

- all Super King™ long shank couplings accept 3 band clamps



Pin Lug Spanner Wrenches

Single End

Size	Plated Iron Part #
2"	SW20
2½"	SW25
3"	SW30
4"	SW40
6"	SW60



Double End

Size	Plated Iron Part #
1½", 2" x 2½", 3"	SW153



- additional spanner wrenches are available on pages 799 - 802