

Hydraulic Hose Couplings Stems

Feature:

- stems have a collar behind the hex to engage fingers



NPTF Size	Plated Steel		Price/E
	Part #		
3/8"	MSC		\$6.30
1/2"	HY4		16.70
3/4"	MS6		9.80
1"	HY8		24.40

NPTF Size	Plated Iron		Price/E
	Part #		
1-1/4"	HY10		\$35.60
1-1/2"	HY12		40.80
2"	HY16		46.85

Clamps

Feature:

- for use only on 1 wire hydraulic hoses



Hose ID	Hose OD		Plated Iron		Torque in ft. lbs.
	from	to	Part #	Price/E	
3/8"	48/64"	50/64"	HD1-3	\$18.00	12
1/2"	56/64"	60/64"	HD1-4	18.00	18
3/4"	1-10/64"	1-14/64"	HD1-6	21.65	18
1"	1-29/64"	1-35/64"	HD1-8	26.10	36

Feature:

- for use only on 2 wire hydraulic hoses



Hose ID	Hose OD		Plated Iron		Torque in ft. lbs.
	from	to	Part #	Price/E	
3/8"	52/64"	56/64"	HD2-3 ¹	\$15.00	12
1/2"	60/64"	1"	HD2-4 ¹	19.60	18
3/4"	1-14/64"	1-18/64"	HD2-6 ¹	19.50	18
1"	1-33/64"	1-39/64"	HD2-8 ¹	30.25	36

¹ parts will become obsolete once inventory is depleted

Feature:

- for use on hydraulic hose with 1, 2 or 4 wire braids or spiral plies




Size	Hose OD		Plated Iron		Torque in ft. lbs.
	from	to	Part #	Price/E	
1-1/4"	1-48/64"	2"	HD2-9 ¹	\$40.00	64
1-1/4"	2"	2-8/64"	HD2-10 ¹	36.75	64
1-1/2"	2-12/64"	2-18/64"	HD2-11 ¹	36.75	64
1-1/2"	2-16/64"	2-20/64"	HD2-12 ¹	38.50	64
2"	2-36/64"	2-48/64"	HD2-15 ¹	58.30	90
2"	2-48/64"	2-58/64"	HD2-16 ¹	59.40	90

¹ parts will become obsolete once inventory is depleted

Features:

- for use only on 1 or 2 wire hydraulic hoses

 This clamp *should not* be used on 4 or 6 wire hydraulic hose even when hose falls within recommended ranges.



Size	Hose OD		Plated Iron		Torque in ft. lbs.
	from	to	Part #	Price/E	
3/8"	50/64"	52/64"	HRC-037	\$17.30	18
1/2"	57/64"	1"	HRC-050	20.60	18
3/4"	1-16/64"	1-20/64"	HRC-075	17.85	36
1"	1-37/64"	1-41/64"	HRC-100	22.70	64
1-1/4"	1-54/64"	1-62/64"	HRC-125	40.00	90
1-1/2"	2-10/64"	2-18/64"	HRC-150	38.30	90
2"	2-43/64"	2-52/64"	HRC-200	49.65	90