

**NEW**  
FOR 2013

## Primator 3000 Monitor



**Features:**

- 4 bolt hole pattern on flange
- 360° horizontal and 160° vertical travel
- other configurations available

Inlet Configuration	Outlet	Waterway	Flow	Weight	Aluminum Part #	Price/E
3" flange	2½" male NST	3"	800 GPM	28 lbs.	<b>PKF16646-300FL</b>	<b>\$4545.00</b>

## Monitor Nozzle



**Features:**

- spinning teeth
- swivel nut
- operating pressure: **100 PSI** (water only) at ambient temperature (70°F)
- 200, 500, 800 GPM at 100 PSI

Size	Thread	Weight	Anodized Aluminum Part #	Price/E
2½"	NST	10 lbs.	<b>PKF0186NST</b>	<b>\$2785.00</b>



## Steel FirePro™ Monitor



**Features:**

- stainless steel discharge tip and ball bearings
- red epoxy finish standard
- 150# ASA raised face 4" flange
- 360° horizontal and 140° vertical travel
- seamless 2½" monitor - rated at 750 GPM
- Factory Mutual approved

Size	Inlet Configuration	Outlet	Waterway	Flow	Weight	Carbon Steel Part #	Price/E
22" x 13"	4" flange	2½" male NST	2½"	750 GPM	50 lbs.	<b>FP475S</b>	<b>\$3400.00</b>



## Master Stream Nozzles



**Features:**

- factory set at 500 GPM
- a straight stream to fog 'quick throw' pattern change
- constant gallonage
- Factory Mutual approved

Size	Thread	Material	Weight	Part #	Price/E
2½"	NST	brass	19 lbs.	<b>FP500B</b>	<b>\$2470.00</b>
2½"	NST	aluminum	---	<b>FP500A</b>	<b>2055.00</b>